



Residential Home, Apartment, & Condo Inspection Checklist Guide

This list is to help prepare for a Valley Park Fire Protection District Residential Occupancy inspection and does not include every possible code violation.

General Health

___ Egress pathways must be clear and accessible.

Furnace

___ Gas shut off installed.

Water Heater

___ Gas shut off installed.

___ Galvanized flue pipe.

Electric Panel

___ Panel is readily accessible - a clear pathway to it.

___ Knock-out covers/plugs/wire clamps installed if needed (inside and outside of panel).

___ All proper screws installed fastening panel cover.

___ Electric service cable & other wires not split or deteriorated.

___ Minimum 8 gage ground wire installed.

___ Electric service drop (From pole) must be minimum 8 feet from any standing surface.

Plumbing Drain Stacks

___ Fire blocking present around ceiling penetrations.

Laundry (serving unit)

___ GFCI outlets installed in laundry area.

Smoke & CO Detectors

___ 1 smoke detector per bedroom, 1 outside of bedrooms in hall, 1 on each level, & 1 in basement (all functioning).

___ All smoke and CO detectors must be under 10 years old.

___ Connected, wired systems must be maintained.

___ 1 CO detector per floor - installed per manufacturer installation instructions.

Kitchen

___ All countertop electrical outlets are GFCI protected.

___ Garbage disposal has a wire clamp - outlet must be on a GFCI.

___ In cabinet wiring must be in conduit or manufacturers plug.

___ Anti-tip device installed for stove.

___ Any outlet serving a counter must be GFCI protected (Including island)

___ No GFCI required for refrigerator only outlet.

Bathrooms

___ All outlets in bathroom must be GFCI.

___ Sink drain & water lines fire blocked.

Windows

___ Stays open when lifted, no broken glass.

Exterior (leading to unit)

___ Outlets GFCI protected in weatherproof cover/box.

___ Walkways, patios, porches don't have trip hazards or cracks 3/4" or larger.

___ A/C electric box doesn't have exposed wiring or open knockout plugs (serving unit).

Hallways & Stairways (leading to & in unit)

___ Stairways have handrails when over 3 steps.

___ Guardrails are present above 30" drop off.

Deck (serving unit)

___ Structurally sound, joist hangers where needed.

Garages (serving unit)

___ Fire rated walls ceiling required in attached garage including gables penetrations to be fire blocked.

___ Fire rated door required to living space in attached Garages (solid wood or fire rated metal).

___ Garage door safety sensor must be present and installed properly.

Other General Guidelines

___ All outdoor, garage, and unfinished areas must have outlets GFCI protected.

___ No exposed wire splices or open junction boxes.

___ No unprotected wiring may be outside of wall cavity or hang below floor joist.

___ Outlets/switches working & have cover plates.

___ No open ground or reverse polarity outlets.

___ 3-pronged outlets are grounded or GFCI protected.

___ Outlets within 6' of a water source GFCI protected.

___ Sump pump outlet needs simplex or GFCI protection.

___ Fire blocking materials present around ceiling & wall penetrations.

___ All doors must be installed and working properly.

___ Interior keyed locks prohibited.

___ All areas must be structurally safe and in good repair.

___ House address numbers shall be 4" minimum high, 1/2" stroke width and visible from the street. Missing numbers shall be replaced. May be located on either house or mailbox.

___ No extension cords are allowed. All fixtures, appliances, etc. must use manufacturers' wiring.

"This list shows common inspection checks and is not all inclusive for every possible code violation. The property should be vacant and void of any furniture, appliances, or belongings that may block inspection areas. Blocked areas may result in a failed inspection. This checklist is provided for informational purposes only. It does not constitute any legal advice."